CHROMA AUSTRALIA PTY LTD ACN 001 594 609

17 MUNDOWI RD

PAGE 1 of 2 DATE of ISSUE: 1 SEPTEMBER 2009

MT KURING-GAI NSW 2080, Australia

TEL: (02) 9457 9922 FAX: (02) 9457 8082

EMERGENCY TEL: AS ABOVE, or Poisons Information Centre

# **Material Safety Data Sheet** Classified as Hazardous According to the Criteria of Worksafe Australia

### **IDENTIFICATION**

Product name CHROMA SATIN SOLVENT VARNISH

U.N. No: 1300

Other names:

Hazchem: 3Y

Dangerous Goods Class & Sub Risk: 3.2

Flash Point (°C): 36°C

Manufacturer's Product Code: **CR72490** 

Poisons Schedule: S5

SOLVENT STRIPPABLE ARTISTS' FINISHING VARNISH

Physical Description/Properties

Appearance: CLOUDY LIQUID Boiling Point/Melting Point (°C) 146°C

Flammability limits (%): N/A

Vapour Pressure (pascals or mm of Hg at 25°C) N/A

Solubility in Water (g/L): **Insoluble** 

Specific Gravity APPROX 0.85 – 0.9g/mL

Other properties

Chemical entity

Ingredients

Use:

CAS No. Proportion

ACRYLATE COPOLYMER COMMERCIAL IN CONFIDENCE 45%-55% MINERAL TURPENTINE 64742-95-6 20%-35% PRESERVATIVE 62530-20-1 2% MATTING AGENT **COMMERCIAL IN CONFIDENCE** 8%-18%

## HEALTH HAZARD INFORMATION

**HEALTH EFFECTS:** 

**ACUTE:** Swallowed MODERATELY TOXIC. MAY CAUSE GASTRIC IRRITATION

NAUSEA/VOMITING & ABDOMINAL PAIN.

MODERATE IRRITATION Eye

Skin REPEATED OR PROLONGED CONTACT MAY LEAD TO DERMATATIC EFFECTS. Inhaled MAY BE HARMFUL. MAY CAUSE IRRITATION TO THE NOSE AND THROAT. VAPOURS CAN CAUSE HEADACHE, DIZZINESS AND POSSIBLE NAUSEA. Chronic: EFFECTS OF EXPOSURE ARE CUMULATIVE. PROLONGED SKIN CONTACT

CAN CAUSE CHRONIC DERMATITIS.

FIRST AID:

RINSE MOUTH THOROUGHLY WITH WATER. GIVE WATER TO DRINK. DO Swallowed

NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

Eve RINSE EYES THOROUGHLY FOR AT LEAST 15 MINUTES.

Skin WASH SKIN WITH SOAP AND WATER.

REMOVE PATIENT FROM AFFECTED AREA TO FRESH AIR. Inhaled

ADVICE TO DOCTOR

TREAT SYMPTOMATICALLY

# PRECAUTIONS FOR USE

### **EXPOSURE STANDARDS**

INHALATION TCLO (HUMAN): 600MG/M³/8H: 1RR (BASED ON PETROLEUM SPIRITS. TLV/TWA 480GM/M³. GUIDELINES FOR GOOD PRACTICE: ATMOSPHERIC CONTAMINATION SHOULD BE KEPT TO AS LOW A LEVEL AS POSSIBLE.

## **ENGINEERING CONTROLS**

TO MAINTAIN LEVELS BELOW THE RECOMMENDED EXPOSURE LIMIT, PRODUCT MUST BE USED IN WELL VENTILATED ROOM/AREA.

### PERSONAL PROTECTION

SAFETY GLASSES OR FACE SHIELD, GLOVES AND APRON

### **FLAMMABILITY**

AVOID ALL IGNITION SOURCES

## SAFE HANDLING INFORMATION

#### STORAGE & TRANSPORT

STORE IN A COOL PLACE AWAY FROM HEAT SOURCES OR IGNITION.

## **SPILLS & DISPOSAL**

REMOVE ALL POSSIBLE SOURCES OF IGNITION. USE ABSORBENT MATERIALS - SAND OR SOIL, SAWDUST ETC. TO CONTAIN SPILL. PLACE IN APPROPRIATELY LABELLED CONTAINER FOR SAFE DISPOSAL. CONTACT LOCAL WASTE DISPOSAL AUTHORITY FOR DISPOSAL METHODS.

## FIRE/EXPLOSION HAZARD

CARBON MONOXIDE. EXTINGUISH FIRES WITH: CO2, DRY CHEMICAL OR FOAM.

## OTHER INFORMATION

DO NOT STORE WITH STRONG OXIDANTS, SUCH AS LIQUID CHLORINE AND SODIUM HYPOCHLORITE.

## **CONTACT POINT**

MT KURING-GAI AUSTRALIA

## **DATE OF ISSUE: 1 SEPTEMBER 2009**